

NEW PRODUCT

DAVEY
StarFlo®
**TOUGH AND
VERSATILE**

APPLICATION

Ideal for in-ground and above ground pools, large swim spas and plunge pools. Also suitable for solar pool heating. Models to suit pools up to 140,000 litres.



DESIGNED TO FILTER AND CIRCULATE POOL WATER

- > **Reliable - Universal, multi-fit and versatile pump that suits multiple applications:**
 - Constructed of strong corrosion resistant and UV resistant materials for long and reliable working life
 - Heavy duty, totally enclosed motor protects against the elements for long operating life
 - Built-in, self-resetting thermal overload protects the motor against damage from over-heating
- > **High Quality** – Corrosion resistant Noryl impeller for longer lasting trouble free performance
- > **Long Lasting** – High performance silicon carbide Viton mechanical seal for long life in pool water
- > **High Strength** – 316 stainless steel motor shaft
- > **High Performance** – Powerful pumping delivering optimum flow rates for rapid pool water turnover
- > **Double insulated to water circuit**
 - Provided with an Equipotential Bonding Point for AS/NZ 3000 wiring standards
- > Fully serviceable, allowing for easy maintenance and repair
- > Drain plugs enabling simple water drainage for easy maintenance
- > 3m power lead with 10amp Australian three pin plug fitted to all models
- > 3 year warranty




Depend on Davey

DAVEY

StarFlo

Universal Pool Pump



40 & 50mm barrel unions
for ease of installation

Easy to remove, see-through strainer lid

Self resetting thermal overload protection
in the event of the pump overheating

Corrosion resistant Noryl impeller for longer
lasting trouble-free performance

316 stainless steel motor shaft
won't corrode or rust


High performance motor with power
reserves for extended operating life

**High performance silicon carbide Viton
mechanical seal** for long life in pool water

ELECTRICAL DATA

Model	DSF300	DSF420
Voltage (V)	220-240	
Phase	Single	
Supply frequency (Hz)	50	
Run current (A)	5.8	8.3
Motor input power (W)	1100	1650
Motor output power (W)	750	1300
RPM	2900	
Enclosure class (IP)	55	
Insulation class	F	
Approval No.	TUV02147EA	

HYDRAULIC PERFORMANCE




OPERATING LIMITS

Max. water temperature	Max. ambient temperature	dBa @ 1 metre
40°C	50°C	62 - (DSF300) 65 - (DSF420)

DIMENSIONS (mm)

Model	Mounting Holes Diameter	Inlet PVC	Outlet PVC	Net Weight (kg)
DSF300	11	40 & 50	40 & 50	10.0
DSF420				11.5



MACKAY (Head Office)

9-15 Industrial Street
MACKAY QLD 4740
+61 (07) 4969 4949
+61 (07) 4969 4900
info@dowdens.com.au

PROSERPINE

4 Pepper Street
PROSERPINE QLD 4800
+61 (07) 4969 4940
+61 (07) 4969 4900
prossy@dowdens.com.au

ROCKHAMPTON

4 / 415 Yaamba Road
NTH ROCKHAMPTON QLD 4701
+61 (07) 4923 6969
+61 (07) 4923 6900
rocky@dowdens.com.au

BRISBANE

24 / 140 Wecker Road
MANSFIELD QLD 4122
+61 (07) 3828 7000
+61 (07) 3828 7055
brisbane@dowdens.com.au